

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number  
**WO 2004/063988 A1**

(51) International Patent Classification<sup>7</sup>: **G06T 5/00**

(21) International Application Number:  
PCT/IB2004/000063

(22) International Filing Date: 12 January 2004 (12.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03290106.8 15 January 2003 (15.01.2003) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ROUET, Jean-Michel** [FR/FR]; 156 Boulevard Haussmann,

F-75008 PARIS (FR). **FRADKIN, Maxim** [IL/FR];  
156 Boulevard Haussmann, F-75008 PARIS (FR).  
**MAKRAM-EBEID, Shérif** [FR/FR]; 156 Boulevard  
Haussmann, F-75008 PARIS (FR).


(74) Agent: **LOTTIN, Claudine**; Société Civile SPID, 156  
Boulevard Haussmann, F-75008 PARIS (FR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **IMAGE PROCESSING METHOD FOR AUTOMATIC ADAPTATION OF 3-D DEFORMABLE MODEL ONTO A SUBSTANTIALLY TUBULAR SURFACE OF A 3-D OBJECT**



A



B

(57) **Abstract:** An image processing method, comprising acquiring an image of a 3-D tubular object of interest to segment; computing a 3-D path that corresponds to the centerline of the tubular object and defining segments on said 3-D path; creating an initial straight deformable cylindrical mesh model, of any kind of mesh, with a length defined along its longitudinal axis equal to the length of the 3-D path; dividing this initial mesh model into segments of length related to the different segments of the 3-D path; computing, for each segment of the mesh, a rigid-body transformation that transforms the initial direction of the mesh into the direction of the related segment of the 3-D path, and applying this transformation to the vertices of the mesh corresponding to that segment. The method comprises avoiding self-intersections in the bent regions of the tubular deformable mesh model and sharp radius changes from one segment of the mesh model to the other, by adapting or modulating the radius of the cylindrical deformable mesh model according to the local curvature of the 3-D path, sample distance of the path points and a predefined input radius.

**BEST AVAILABLE COPY**

WO 2004/063988 A1